

6

5

4

3

2

1

Renxin.Thermal
www.renxin-precision.com

Versions	Notes	Engineer	Date

16.0

18.0

21.5

23.5

2xØ1.3

30.0

18.3

4.5

1.3

M3

Rth(K/W)

20

15

10

5

20

25

30

35

40

mm

RX580-016-A4

Flow Process List

1	
2	
3	
4	
5	
6	
7	
8	

PN
RX580-016-A4

Drw
RX580-016-00

Material
AL6063-T5

Ref

Rev 1

Units:mm

ISO2768-M

Finish
black anodize

Weight(g)
0.31 Kg/meter

Sheet
1

A4

机械加工尺寸容许公差

0 ~ 6	±0.1
6 ~ 30	±0.2
30 ~ 120	±0.3
120 ~ 400	±0.8
角度	±1°

Flow Process List	
1	
2	
3	
4	
5	
6	
7	
8	

Renxin Thermal Solutions
仁信精工实业有限公司
Renxin-Seiko Industry Co., Ltd
T+86 769 8182 2159 F:+86 769 8182 2157
[Http://www.renxin-precision.com](http://www.renxin-precision.com)

Description Heatsink with solder pins PCB mounting for TO 220				PN RX580-016-A4		Units:mm			
CAT		Area	114.75 mm ²	Drw RX580-016-00		ISO2768-M			
Design	LXG	Perimeter		Material AL6063-T5	Finish black anodize				
Approval		Scale	2:1	Ref	Weight(g) 0.31 Kg/meter				
Date	2016-08-21	Mount		Rev 1	Sheet	1	A4		